


SLE4000

Infant Ventilator with
touch-screen operation



 **SLE**

When the smallest thing matters



Designed for Neonates

Neonatal ventilation poses real challenges to neonatologists and caregivers. Neonatal patients, especially premature infants are very fragile and have undeveloped respiratory systems that require very small tidal volumes. Therefore, precision and reliability are crucial. Triggered modes of ventilation, require the finest technology to ensure reliable detection of the baby's breathing. Fast triggering of mechanical breaths is essential, in order to reduce the patient's work of breathing.

In the busy NICU environment, medical and nursing staff need a ventilator that provides them with all the tools they need to treat their most challenging patients.

The ventilator needs to be intuitive and require minimum amount of training to use effectively. The patient is always the main focus and technology is the means to achieve a good outcome.

The SLE4000 infant ventilator is the result of years of experience in the field of Neonatal ventilation and it was designed with all this experience in mind.

The SLE4000 is a dedicated neonatal ventilator that addresses all the challenges of neonatal ventilation.

Sophisticated & Powerful



Version 5
Software



Targeted Tidal
Volumes



Open Lung
Concept



Valveless
System



Hot Wire
Flow Sensor

Targeted Tidal Volume plus (TTV^{plus})

Recent research indicates that the use of volume targeted ventilation offers significant improvement in ventilation outcomes, such as reduction of death, air leak syndrome and chronic lung disease, compared to pressure limited ventilation.⁽¹⁾

In TTV^{plus}, the SLE4000 measures the expired tidal volume (V_{te}) and adjusts the PIP in accordance with the changing lung mechanics, to deliver the user-set V_{te} at the user-set T_i.

A new algorithm further improves the stability of delivered volumes and ensures delivery of the breath at the user set T_i.

The latest software adds ET tube leak compensation of up to 50% and automatic adjustment of PIP according to an individual patient's lung mechanics. Additionally, optimisation of the alarm system reduces nuisance alarms.

Pressure Support Ventilation (PSV)

PSV is a mode of ventilation where the baby has control of the start and the termination of inspiration. This level of interaction leads to better patient synchrony.

The SLE4000 boasts an automatic leak compensation algorithm that will ensure flow termination even at the presence of a leak.

PSV is also available in SIMV. By pressure supporting spontaneous breathing, the SLE4000 helps reducing the work of breathing of the baby, potentially leading to faster and successful weaning.⁽²⁾

Nasal CPAP

The SLE4000 can be used with nasal prongs, giving the user even more options for weaning babies and supporting them immediately after extubation.

Respiratory Mechanics Measurement


Loops and waveforms allow the clinician to monitor and adjust ventilator strategy.

- Real-time lung dynamics
- Loops can be displayed in real time or frozen
- Breath-by-breath display of resistance, compliance and C10/C values


References

1. Work of breathing during SIMV with and without pressure support. Deena Shefali Patel, Gerrard F Rafferty, Silke Lee, Simon Hannam and Anne Greenough: Arch. Dis. Child. Published online 17 Feb 2009; doi:10.1136/adc.2008.152926
2. Volume-targeted versus pressure-limited ventilation in the neonate. Wheeler K, Klingenberg C, McCallion N, Morley CJ, Davis PG: Cochrane Library 2010, Issue 11

Targeted Tidal Volume




Pressure Support Ventilation




Without flow termination

With flow termination

Respiratory Mechanics Measurement





Audible and Visual Alarms

The alarm panel provides an immediate audible and pictorial view of the alarm condition, thus allowing easy monitoring, plus an alarm history of the last 100 conditions.

Integrated battery

The SLE4000 has an internal battery that ensures uninterrupted operation in case of a mains supply failure. The battery lasts for more than one hour in normal operation conditions. This makes the ventilator even safer and makes it ideal for use in internal hospital transport.

Patient Circuit Connections

Front panel mounted patient circuit connections with autoclavable exhalation block.

Unmatched Ease of Use

At SLE, we believe that the User should be able to concentrate on the most important part of their job: look after their patients. That's why the SLE4000 has been designed to be so intuitive and easy to use.

New users find the transition to the SLE4000 seamless. Most of them only require a minimum amount of training to use the SLE4000 effectively. Considering the potential of the SLE4000, this is a huge achievement.

Quality Build

The SLE4000 case is manufactured in a unique solid cast polyurethane moulding. This tough material is ideal for use in a busy neonatal unit and easily withstands the knocks and bumps of everyday life.



Safe & Easy-to-Use

Integral screen

Colour-coded user touch screen. Easy-to-use, logical sequence allowing quick, smooth adjustments.

The SLE4000's 12.1 inch screen means that all the data you need can be easily seen.

Real-time Data Display

Real-time lung mechanics measurements and ventilatory data.

This allows for continuous feedback for making crucial clinical decisions.

Pre-Setting Facility

Parameters can be preselected for the next mode whilst continuing to ventilate the patient in the current mode of ventilation.

Compact Unit

The SLE4000 ventilator is housed in a single compact box, making it easier to clean and use.

The integrated touch screen is angled for perfect visibility and easy to read from a distance.

Unique Interface

SLE has worked hard to deliver the best User Interface in the market. Thought has been given to all aspects of the user scenarios. Some of the things that make the SLE4000 User Interface so intuitive, innovative and unique:

- Full touch operation
- Logical layout of the different sections
- Minimal number of sub-menus
- Easy-to-read characters
- Colour-coding of controls



Valveless System

All of SLE's ventilators use 'valveless technology'. This means that the management of the airflow is controlled not by a mechanical valve, but by a jet of air, acting as a pneumatic piston. This system is based on 20 years of patented technology, and offers many significant advantages.

The first of these is that there is no additional resistance in the circuit. This ensures that even with the smallest of babies there is minimal resistance to flow and the Work of Breathing is kept to a minimum.

The high-speed air jets also mean that the system is very reactive allowing very precise control of the airflow with none of the problems of inertia and sticking associated with conventional valves.

The simplicity of the design - a single exhalation block and exhaust manifold also mean that cleaning and assembly are much simplified and reduce the chances of infection or mis-assembly.

Technology

The SLE4000 measures flow and volume using a hot wire technology sensor, designed to be placed proximally to the patient, which is essential for the accuracy on neonates.

Using a small, lightweight sensor with less than 1 ml of additional deadspace ensures minimal interference with breathing.

Upgradeable

The SLE4000 is a modern, sophisticated ventilator operating with advanced software.

This ensures that your ventilator can always be upgraded and incorporate new features that are dictated by advances in the clinical field as well as feedback from our customer base across the world.

Reliable

SLE's goal is to always provide the best quality products. This is why we always work to improve the performance, reliability and consistency of our components.

In recent years, we have developed quieter valves, made our ventilators run cooler, added processing power, reduced maintenance costs, made servicing easier and introduced a brand new flow sensor.

Our customers can be sure that SLE will not only maintain the high standards that we have set, but keep raising the bar...

Smart &
Cost-Effective

Specifications

Ventilation Modes

CPAP / PTV / PSV

Inspiratory Time:	0.1 to 3.0 s
CPAP Pressure:	0 to 20 mbar
Inspiratory Pressure:	0 to 65 mbar
Volume Targeting:	2 to 200 ml
O ₂ :	21% to 100%

CMV / SIMV

BPM:	1 to 150
I:E Ratio:	(11.2:1 to 1:600)
Inspiratory Time:	0.1 to 3.0 sec
PEEP Pressure:	0 to 20 mbar
Inspiratory Pressure:	0 to 65 mbar
Volume Targeting:	2 to 200 ml
O ₂ :	21% to 100%

Monitoring Parameters

Measurement of Flow and Volume

Flow Sensor Type:	10 mm dual-hot-wire anemometer (autoclavable or single use)
Flow Rate:	0.2 to 32 l/min (Accuracy ±8%)
Expiratory Tidal Volume:	0 to 999 ml
Expiratory Minute Volume:	0 to 18 litres
Deadspace:	<1 ml
Weight:	<10 g
Tube Leakage:	0 to 99% (Resolution: 1%, Averaged over 10 breaths)
Breath Rate (total):	0 to 150 BPM
Dynamic Compliance:	0 to 100 ml/mbar (Resolution: 1 ml/mbar)
C20/C:	Resolution 0.1
Sampling Time:	2 ms
Resistance:	0 to 1000 mbar.second/l
Triggering:	Inspiratory flow (0.2 to 10 l/min)

The above values are measured under ATPD (ambient temperature and pressure, dry) conditions.

Oxygen Concentration

Range:	21 to 100% (Resolution 1%)
--------	-------------------------------

Pressure

Real-time Pressure measurement:	Resolution 1 mbar
Sampling time:	2 ms
Peak Pressure:	0 to 175 mbar (resolution 1 mbar)
PEEP Pressure:	0 to 175 mbar (resolution 1 mbar)
Mean Pressure:	-175 to 175 mbar (resolution 1 mbar)

User Settable Alarms:

High Pressure

Autoset when patient pressure controls are adjusted or can be manually adjusted.

Range:	10 to 110 mbar
Resolution:	0.5 mbar

Cycle Fail

Autoset when patient pressure controls are adjusted or may be manually adjusted.

Low Pressure

Autoset when patient pressure controls are adjusted or can be manually adjusted.

Range:	-10 mbar to 10 mbar below high pressure threshold
--------	--

High Tidal Volume

Range:	3 to 200 ml
Resolution:	0.2 ml

Low Tidal Volume

Range:	0 to 200 ml
Resolution:	0.2 ml

High Minute Volume

Range:	0.02 to 18 litres
Resolution:	0.1 litre

Low Minute Volume

Range:	0 to 0.02 litres below High Minute Volume threshold
Resolution:	0.1 litre

Apnoea time

Settable only in CPAP or when Backup rate is less than 10 BPM.

Range:	5 to 60 sec
Resolution:	1 second

Technical Specifications

Power Requirements

Voltage :	100-240 V 50-60 Hz
Power :	115 VA
Battery back up:	12V, 45-60 minutes (dependant on mode of operation)
Battery charging:	Full charge 24 hours, 80% charge after 8 hours

Outputs

RS-232C

Air and O₂ input

Pressures:	2.8 - 6 bar
Fresh Gas Flow:	8 litres/min
Maximum gas flow:	60 litres/min

Operating Environment

Temp:	10 - 40 °C
Humidity:	30 - 75% (non- condensing)

Dimensions

Size, ventilator only:	330mm W x 330mm H x 470mm D
Height on trolley:	1140 mm
Weight, ventilator only:	22.1 kg

Constructed to conform to:

Designed and manufactured to conform to all relevant international standards for medical devices for the countries in which it is sold.

Data subject to change without notice.

Environmental storage conditions

When packed for transport or storage:
Ambient Temperature: -40 °C to +70 °C
Relative Humidity: 10% to 90%
(non-condensing)
Atmospheric Pressure: 500 hPa to
1060 hPa

SLE is a world leader in the design and manufacture of neonatal ventilators.

Years of ventilation experience have given the company an understanding of the challenges that nurses and clinicians face when caring for the tiniest and most critical babies.

From being the pioneers of neonatal Patient Triggered Ventilation (PTV) in the 1980s, to the introduction of combined HFO (High Frequency Oscillation) in the 1990s, and the design of the first touch-screen Neonatal Ventilator in the 2000s, SLE has maintained a position of strength in neonatal ventilation.

The company's guiding principle is to support clinical and nursing staff in their everyday work.

The knowledge and experience gained during years of development is manifested in the SLE4000 ventilator: the result of SLE's ongoing commitments to innovation, competency and care.



SLE Limited.
Twin Bridges Business Park, 232 Selsdon Road,
South Croydon Surrey CR2 6PL UK
Telephone: +44 (0)20 8681 1414 • Fax: +44 (0)20 8649 8570
E-mail: sales@sle.co.uk • Web: www.sle.co.uk



www.sle.co.uk